

Here are the tip trimming instructions for almost every golf shaft on the market! Whether it be graphite or steel we have the correct numbers for you! Use the numbers shown or slightly deviate from them for even more customization! Good luck!

**TIP TRIMMING INSTRUCTIONS FOR GRAPHITE IRON SHAFTS**

	1	2	3	4	5	6	7	8	9	PW	SW
Pre-Flexed	0"	0"	.25"	.50"	.75"	1.0"	1.25"	1.50"	1.75"	2.0"	2.25"
Combo R/S for R Flex	0"	0"	.25"	.50"	.75"	1.0"	1.25"	1.50"	1.75"	2.0"	2.25"
Combo R/S for S Flex	2.0"	2.0"	2.25"	2.50"	2.75"	3.0"	3.25"	3.50"	3.75"	4.0"	4.25"
Combo A/L for L Flex	0"	0"	.25"	.50"	.75"	1.0"	1.25"	1.50"	1.75"	2.0"	2.25"
Combo A/L for A Flex	2.0"	2.0"	2.25"	2.50"	2.75"	3.0"	3.25"	3.50"	3.75"	4.0"	4.25"

**TIP TRIMMING INSTRUCTIONS FOR GRAPHITE WOOD SHAFTS**

	1	3	5	7	9
Pre-Flexed	0"	.50"	1.0"	1.5"	2.0"
Combo R/S for R Flex	0"	.50"	1.0"	1.5"	2.0"
Combo R/S for S Flex	2.0"	2.5"	3.0"	3.5"	4.0"
Combo A/L for L Flex	0"	.50"	1.0"	1.5"	2.0"
Combo A/L for A Flex	2.0"	2.5"	3.0"	3.5"	4.0"

**NOTE:** These numbers are for standard length shafts. Adjustments must be made according to length.

Butt cut to length

**TIP TRIMMING INSTRUCTIONS FOR STEEL IRON SHAFTS**

	1	2	3	4	5	6	7	8	9	PW	SW
Pre-Flexed	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	4.0"	4.5"
Combo R/S for R Flex	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	4.0"	4.5"
Combo R/S for S Flex	2.0"	2.0"	2.5"	3.0"	3.5"	4.0"	4.5"	5.0"	5.5"	6.0"	6.5"
Combo A/L for L Flex	0"	0"	.5"	1.0"	1.5"	2.0"	2.5"	3.0"	3.5"	4.0"	4.5"
Combo A/L for A Flex	2.0"	2.0"	2.5"	3.0"	3.5"	4.0"	4.5"	5.0"	5.5"	6.0"	6.5"

**TIP TRIMMING INSTRUCTIONS FOR STEEL WOOD SHAFTS**

	1	3	5	7	9
Pre-Flexed	0"	1.0"	2.0"	3.0"	3.5"
Combo R/S for R Flex	0"	1.0"	2.0"	3.0"	3.5"
Combo R/S for S Flex	2.0"	3.0"	4.0"	5.0"	5.5"
Combo A/L for L Flex	0"	1.0"	2.0"	3.0"	3.5"
Combo A/L for A Flex	2.0"	3.0"	4.0"	5.0"	5.5"



### Fitting Guide

Use the following methods to help determine which flex is right for you! Use one method for a quick easy answer, or use all three and compare your findings!

YDS CARRIED WITH DRIVER	RECOMMENDED FLEX AT DISTANCE CARRIED	SWING SPEED W/ DRIVER (MPH)	RECOMMENDED FLEX AT SWING SPEED	IRON USED TO CARRY 150 YDS	RECOMMENDED FLEX AT DISTANCE CARRIED
260+	(X)	115 or above	(X) Slightly Tip Trimmed	PW	(X)
250	(S) Slightly Tip Trimmed	105 to 115	(X)	9 iron	(S) Slightly Tip Trimmed
240	(S)	100 to 105	(S) Slightly Tip Trimmed	8 iron	(S)
230	(R) Slightly Tip Trimmed	95 to 100	(S)	7 iron	(R) Slightly Tip Trimmed
220	(R)	90 to 95	(R) Slightly Tip Trimmed	6 iron	(R)
210	(A) Slightly Tip Trimmed	80 to 90	(R)	5 iron	(A) Slightly Tip Trimmed
200	(A)	70 to 80	(A) Slightly Tip Trimmed	4 iron	(A)
190	(L) Slightly Tip Trimmed	60 to 70	(A)	3 iron	(L)
180	(L)	40 to 60	(L)		

CALL TOLL FREE TO ORDER: 800-236-4566